

MATERIAL SAFETY DATA SHEET**1. [CHEMICAL PRODUCT & COMPANY IDENTIFICATION]**

CHEMICAL PRODUCT NAME : HITACHI CHEMICAL MOLDING COMPOUND,
CEL-9210HF series

NAME OF MANUFACTURER : HITACHI CHEMICAL Co.,Ltd

ADDRESS : 1772-1 Kanakubo.Yuki Ibaraki 307-0015 Japan

NAME OF SECTION : Semiconductor Materials Div. : H.Yoshizawa

TEL.No. : +81-296-32-8111, FAX No. : +81-296-32-8381 (Japan)

2. [COMPOSITION/INFORMATION ON INGREDIENTS]

SUBSTANCE/MIXTURE : MIXTURE

INGREDIENTS AND COMPOSITION :

Chemical Name	Composition	Chemical Formula	CAS No.
Epoxy Resin-1	1 - 5%	-	Trade secret
Epoxy Resin-2	0.5 - 3%	-	Trade secret
Phenol Resin	2 - 6%	-	Trade secret
Carbon Black	approx. 0.2	C	1333-86-4
Silica	85 - 92%	SiO ₂	60676-86-0
Others	max.2%	-	-

UN CLASS AND UN NUMBER : Not applicable

3. [HAZARDS IDENTIFICATION]

CLASS NAME OF HAZARDOUS CHEMICALS FOR MSDS IN JAPAN

: Miscellaneous dangerous substance

PHYSICAL AND CHEMICAL HAZARDS : No data of mixture

ADVERSE HUMAN HEALTH EFFECTS : No data of mixture

4. [FIRST-AID MEASURES]

EYE CONTACT :Gently rinse the affected eyes with clean water for at least 15 minutes. Immediately call for a physician.

SKIN CONTACT :Thoroughly wash material off the skin with soap and water. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

INHALATION :If affected, move individual to fresh air, if breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, calm, and seek immediately medical attention.

INGESTION :Try to vomit and rinse mouth with water. Give the person plenty of water and arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

5. [FIRE-FIGHTING MEASURES]

EXTINGUISHING MEDIA : Dry chemical powder, carbon dioxide, foam, dry sand.

SPECIFIC HAZARDS WITH REGARD TO FIRE-FIGHTING MEASURES :

- Dry chemical powder, carbon dioxide or dry sand should be used for small fires.
- Apply water from a safe distance to cool and protect surrounding area. Move container from fire areas if it can be done without risk.
- Firefighters should wear proper protective equipments.
- Evacuate personnel from area of fires.

{EMC CEL-9210HF series }

6. [ACCIDENTAL RELEASE MEASURES]

- Sweep up in a bag and clean up by a vacuum cleaner.
- Wear proper protective equipments .
- Wipe off residual spill using paper soaked with methanol or acetone.
- Consult an expert on the disposal of recovered material.

7. [HANDLING AND STORAGE]

- Wear proper protective equipments to avoid direct contact and inhalation.
- Use with local exhaust ventilation.
- Keep the products sealed and kept in the cold room, away from direct sunlight and under the Temperature of 5°C.

8. [EXPOSURE CONTROL / PERSONAL PROTECTION]

CONTROL PARAMETERS :

- ACGIH TLV (2000) TWA 0.1mg/m³(SILICA)

ENGINEERING MEASURES :

- Do not use in areas without adequate ventilation and local exhaust ventilation.
- Set up the shower and the washing eyes equipment near the working area.

PERSONAL PROTECTIVE EQUIPMENTS :

- RESPIRATORY PROTECTION : Dustproof mask.
- EYE PROTECTION : Safety goggles or face shield.
- HAND,SKIN AND BODY PROTECTION : Chemical-resistant gloves boots and apron.

9. [PHYSICAL & CHEMICAL PROPERTIES]

- APPEARANCE : Gray tablet or powder(product).
- DENSITY : 1.98~2.10product)
- BOILING POINT : 2230°C(SILICA)
- MELTING POINT : 1710°C(SILICA)
- DECOMPOSITION POINT : approx. 300°C(product)
- MELTING POINT : 70~80°C(product)
- VAPOR PRESSURE : No data
- SOLUBILITY IN WATER : Not soluble(product)

10. [PHYSICAL HAZARD(STABILITY & REACTIVITY)]

This product is considered a stable material under normal and anticipated storage and handling condition.

PHYSICAL HAZARD	PRODUCT
FLASH POINT (°C)	-)
AUTOIGNITION TEMP. (°C)	approx.600°C

*) UL-94 V-0(EQUIVALENT)

11. [TOXICOLOGICAL INFORMATION]

TOXICOLOGICAL INFORMATION OF EPOXY RESIN-1

- CORROSIVE AND IRRITANT PROPERTIES : I MAY CAUSE IRRITATION TO EYES, SKIN OR RESPIRATORY TRACT.
- MUTAGENIC EFFECTS: POSITIVE IN THE AMES TEST, POSITIVE IN THE CHROMOSOMAL ABERRATION TEST
- TOXITY TEST (28DAYS REPEATING ORAL ADMINISTRATION):
RAT: NOEL 40mg/kg/day

TOXICOLOGICAL INFORMATION OF SILICA

- ROUTE OF ENTRY : It may cause absorption in the body by inhalation, dermal and oral.
- CORROSIVE AND IRRITANT PROPERTIES : It is irritating to eyes skin, mucous membrane and respiratory tract. Repeated or prolonged contact may cause dermatitis.
- ACUTE TOXICITY : No data available.
- CARCINOGENIC EFFECTS IARC : Group 3
- MUTAGENIC EFFECTS : No data available.

TOXICOLOGICAL INFORMATION OF Carbon Black

- ACUTE TOXICITY : Oral LD50(rat) > 8,000mg/kg
Eye contact (Rabit) Non-Irritative
Skin contact (Rabit) Non-Irritative
- ALLERGENIC AND SENSITIZING EFFECTS : No data available
- CARCINOGENIC EFFECTS IARC : Group 2B
ACGIH : Group A4

12. [ECOLOGICAL INFORMATION]

- No data

13. [DISPOSAL CONSIDERATION]

Please follow your country and your region requirements for waste disposal.

14. [TRANSPORT INFORMATION]

Please follow the notes of treatment and storage.

15. [REGULATORY INFORMATION]

It is your responsibility to obtain the regulatory information with regard to this substances from the authority in your country/state/district, etc.

16. [OTHER INFORMATION]

INQUIRY OF THE INFORMATION CONTAINED HEREIN :

Hitachi Chemical Co.,Ltd.
Semiconductor Materials Div. : H.Yoshizawa
Tel.No. ; +81-296-32-8111(Japan)

The information herein is given in good faith, but not warranty, expressed or implied, is made. Please consult Hitachi Chemical Co.,Ltd. for further information.

The information contained herein are, to the best of Hitachi Chemical Company's knowledge and belief, accurate and reliable as of the data issued. It is the user's responsibility to determine the suitability of this information for the adoption of necessary safety precautions. We reserved the right to revise MSDS periodically as and when new information is available.